

Product Data Bulletin

MPI 3100 Glossy Economy Calendered (Revision 0)

Dated: 05/12/04

Description:

Avery Dennison™ MPI 3100 Film is a flexible, white glossy calendered vinyl film. MPI 3100 offers exceptional value for applications requiring a glossy mid-term durable product combined with permanent adhesive performance. MPI 3100 is especially well suited for applications such as Point of Purchase, Product Identification Labels, Medium Term OEM Decals as well as Outdoor and General Signage.

Construction:

Face Film:	3.2 mil (81 m) glossy calendered vinyl film
Adhesive:	Permanent, clear, acrylic pressure-sensitive
Release Liner:	70# Kraft

Physical Properties:

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose (Data represents averages and is not intended for use as a specification).

Recommended Print Method:	Solvent Inkjet (Reference IB #5.80 for printer compatibility.)
Outdoor Durability:	Up to 4 yrs. when properly processed and applied (vertical exposure, unprinted film).
Minimum Surface/Ambient Air Application Temperature:	50° F (10° C)
Application Surface:	Flat or simple curves
Service Temperature Range:	-40° F to 176° F (-40° C to 80° C) (Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions).
Typical Film Caliper (w/adhesives):	4.0 mils (109 µm)
Chemical Resistance:	Resistant to most mild acids, alkalis and salt solutions
Shelf Life:	One year when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.
Dimensional Stability	Good. Determined by measuring shrinkage of film applied to 35 in. ² (232 cm ²) aluminum test panel after 72 hrs. aging at 73° F (23° C) and 50±5% R. H. followed by 48 hrs. at 150° F (65°C)



Product Data Bulletin

Typical Converting Methods:

Thermal Die-Cutting:	Yes, 290° F - 300° F (143° C to 149° C) for 0.5 - 1.0 second. Cutting temperatures and dwell times will vary with differences in die configuration and individual machines. Always test prior to production.
Steel Rule Die-Cutting	Yes

Revisions have been italicized.

Avery Dennison™ is a registered trademark of Avery Dennison Corp.

WARRANTY: All statements, technical information and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that Purchaser has independently determined the suitability of such products for its purposes. Avery Dennison products are warranted to be free from defects in material and workmanship for either one year (or the period stated on the specific product information literature in effect at time of delivery, if longer) from date of shipment if said product is properly stored and applied. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited to repair or replacement of defective product without charge at Avery Dennison's plant or at the location of product (at Avery Dennison's election), or in the event replacement or repairs is not commercially practical, to Avery Dennison's issuing Purchaser a credit reasonable in light of the defect in the product.

Avery Dennison's liability for defective products shall not exceed the purchase price paid therefore by Purchaser and in no event shall Avery Dennison be responsible for any incidental or consequential damages whether foreseeable or not, caused by defects in such product, whether such damage occurs or is discovered before or after replacement or credit, and whether or not such damage is caused by Avery Dennison's negligence.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE (EXCEPT AS TO TITLE), OTHER THAN THOSE EXPRESSLY SET FORTH ABOVE WHICH ARE MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

